

Product Highlights

Efficient and flexible

- ★ Joystick control for turning and walking, easy to operate
- ★ Can turn unilaterally and in place, with flexible maneuverability
- ★ Supports one button automatic leveling, strong adaptability to the venue, safe

Excellent performance

- ★ Rubber tracked chassis, suitable for various complex road surfaces
- ★ Maintenance-free battery with strong battery life
- ★ Electric drive, zero emissions, high efficiency

Low operating costs

- ★ Drawer type structure, convenient and fast maintenance and repair of key components
- ★ Faults diagnosis system, intelligent and efficient



Standard Features



Tilt alarm system	Charging indicator	Buzzer
Diagnosis system	AC power to platform	Flash light
Explosion-proof of the tubing	Manual box	Fault code display
Automatic brake system	Emergency lower	Motion alarm
Safety support bar	Manual brake release	Forklift and lifting holes
Non-marking rubber crawler	Maintenance free battery	
Hour meter, battery display	Proportional Control	

Options Features

Top limit protection auto-stop device	GPS	Electrophoretic coating process
Overload sensor	Platform work light	
Power socket to platform	Foot switch	



Model	XE60MINI CT	
Dimension	Metric	Imperial
Max. Working Height	6.4m	20ft 12in
A Max. Platform Height	4.4m	14ft 5in
B Max. Outreach	0.55m	1ft 10in
C Length Stowed	1.5m	4ft 11in
D Width Stowed	0.78m	2ft 7in
Height Stowed (guardrails folded)	1.74m	5ft 9in
E Height Stowed (guardrails unfolded)	2.06m	6ft 9in
Ground Clearance	0.1m	0ft 4in
Platform Size(L×W×H)	1.28m*0.76m*1.1m	4ft2in×2ft6in×3ft7in
Crawler Size	150*72B-42 Section	150*72B-42 Section
Performance		
Lifting Capacity	230kg	507 lb
Lifting Capacity (extended platform)	100kg	220lb
Max. Load number	2 pers	2 pers
Drive Speed	1.7km/h	1.1mph
Rising Time	23s	23s
Lowering Time	19s	19s
Gradeability	25%	25%
Tilt Sensor (front to back)	3°	3°
Tilt Sensor (side to side)	1.5°	1.5°
Max. Lateral Force	400N	90 lbf
Max. Wind Speed	0	0
Power		
Power Unit Motor (voltage/power)	24V/0.8kw	24V/0.8kw
Hydraulic Tank Capacity	2L	0.5 gal
Battery Specifications	114Ah	114Ah
System Voltage	24V	24V
Control Voltage	24V	24V
Charger (Input Voltage/Output Current)	100-240V/15A	100-240V/15A
Drive motor (voltage/power)	15VAC/1kW	15VAC/1kW
Drive model	Electric	Electric
Weight		
Weight	890kg	1962 lb
Standard	GB/CE	GB/CE



The images in this manual are for illustration only, and all copyrights belong to our company. Due to continuous technological updates, product parameters may change without prior notice.



tall
美通重工
区
ame

Mantall
美通重工 XE60CT

Mantall® 美通重工

Mantall® 美通重工

Mantall®