

XE MINI SERIES
XE 75MINI
ELECTRIC SELF-PROPELLED MINI SCISSOR LIFT

Product Highlights

High performance

- ★Large turning angle and flexible operation in narrow space.Front wheel drive does not slip
- ★The double-sided door design is convenient for maintenance
- ★Low voltage warning improves battery life
- ★Security protection system
- ★Reasonable arrangement of oil pipes with long service life
- ★Wide voltage charger with good adaptability
- ★Large capacity batteries have a long working time
- ★Large ground clearance and good passability
- ★Hydraulic/electric dual drive, meeting different markets

Convenient maintenance

- ★Universal and easy to maintain components
- ★Protected well and easier to clean



Standard Features

Self-lock gate on platform	Forklift holes and lifting holes	Tilt alarm
Non-marking tires	AC power to platform	Automatic pothole protection
Emergency lowering down	Extended Platform	Maintenance free battery
Diagnosis system	Foldable guardrails	
Flash light	Emergency stop button	

Options Features

Power socket to platform	Top-stop sensor
Electrophoretic coating process	GPS





XE MINI SERIES

XE75MINI

ELECTRIC SELF-PROPELLED MINI SCISSOR LIFT

Model	XE75MINI	
Dimension	Metric	Imperial
Max. Working Height	7.6m	24ft 11in
A Max. Platform Height	5.6m	18ft 4in
B Max. Outreach	0.6m	1ft 12in
C Length Stowed	1.48m	4ft 10in
Length - Platform Extended	1.97m	6ft 6in
D Width Stowed	0.81m	2ft 8in
E Height Stowed (guardrails unfolded)	2.16m	7ft 1in
Height Stowed (guardrails folded)	1.78m	5ft 10in
F Wheelbase	1.16m	3ft 10in
Ground Clearance	0.07m	0ft 3in
Pothole protection board ground Clearance(down)	0.02m	0ft 1in
Platform Size(L×W×H)	1.37m×0.7m×1.2m	4ft6in×2ft4in×3ft11in
Skirting Board Height	0.15m	0ft 6in
Performance		
Max. Load number (indoor)	2 pers	2 pers
Lifting Capacity	230kg	507 lb
Lifting Capacity (extended platform)	120kg	265 lb
Drive Speed (Stowed)	3km/h	1.9mph
Drive Speed (Raised)	0.5km/h	0.3mph
Rising Time	32s	32s
Lowering Time	27s	27s
Gradeability	25%	25%
Turing Radius(inside/outside)	0.45m/1.79m	0.45m/1.79m
Tilt Sensor - Front to Back	3°	3°
Tilt Sensor - Side to Side	1.5°	1.5°
Tire Specification/ Type	305mm×114mm	12in × 4.5in
Power		
Drive Model	Hydraulic Drive, 2WD×2WS	Hydraulic Drive, 2WD×2WS
Power Unit Motor (voltage/power)	24V/3.3KW	24V/3.3KW
Hydraulic Tank Capacity	4L	1.1 gal
Battery Specifications	2×12V/115Ah	2×12V/115Ah
Control Voltage	24V	24V
Charger (Input Voltage/Output Current)	100-240V/15A	100-240V/15A
Weight		
Weight	1266kg	2791 lb
Standard	GB/CE	GB/CE



The images in this manual are for illustration only, and all copyrights belong to our company. Due to continuous technological updates, product parameters may change without prior notice.



Mantall
XE75MINI

Mantall
AERIAL WORK PLATFORMS
全新升级
性能更出众
New Upgrade
More Outstanding
Performance
XE75MINI
800-888-8888